



Magnetic grippers

HGR-SQ-040-FL-RH-M-F

Article number: TPGC040378

Product Features

Description	Magnetic gripper
Article number	TPGC040378
Product key	HGR-SQ-040-FL-RH-M-F
Size	40 mm
Specific application	Suitable for high temperatures
Switching	Pneumatic: 2 compressed air connections or, 1 vacuum connection: see 'Gripper connection for vacuum control' (Document tab)
Advised working load	60 N (under ideal conditions - with safety factor 3 acc. EN13155)
Max. tear off force	185 N (under ideal conditions - Graph: see Downloads tab - Factors influencing lifting capacity: see /solutions/magnetic-handling)
Min. advised sheet thickness	2 mm
Interface/connection dim's	Threaded hole M5 (4x), Threaded hole M8
Connections	Pneumatic: M5 (2x)
Material housing	Aluminium, AISI316L (SS 1.4404) (screw cap)
Surface treatment/finishing	Nickel plated
Colour	Grey
Min./max. ambient temperature	0 to 120 °C
Switching pressure	4 bar (recommended), 6 bar (max.), Vacuum pressure -0.3 bar (switch on)
Magnetic system	4 Permanent magnet poles
Magnet quality	Neodymium GSN-38EH, Br 12,600 gauss (at 20 °C), Tmax. 180 °C
Depth	40 mm
Width	40 mm
Height	63 mm
Weight	0.22 kg
Type	High temp.
Air consumption	0.160 l/cycle (1x up, 1x down)