



Magnetic grippers

HGR-SQ-070-FL-R-G-S

Article number: TPGC070078

Product Features

Description	Magnetic gripper
Article number	TPGC070078
Product key	HGR-SQ-070-FL-R-G-S
Size	70 mm
Switching	Pneumatic: 2 compressed air connections or, 1 vacuum connection: see 'Gripper connection for vacuum control' (Document tab)
Advised working load	175 N (under ideal conditions - with safety factor 3 acc. EN13155)
Max. tear off force	530 N (under ideal conditions - Graph: see Downloads tab - Factors influencing lifting capacity: see /solutions/magnetic-handling)
Min. advised sheet thickness	2 mm
Interface/connection dim's	Threaded hole M6 (8x), Threaded hole M10
Connections	Pneumatic: G1/8" (2x)
Material housing	Aluminium, AISI316L (SS 1.4404) (screw cap)
Surface treatment/finishing	Anodized
Colour	Red
Min./max. ambient temperature	0 to 70 °C
Switching pressure	Max. 4 bar, Vacuum pressure -0.3 bar (switch on)
Magnetic system	6 Permanent magnet poles
Magnet quality	Neodymium GSN-45, Br 13,700 gauss (at 20 °C), Tmax. 80 °C
Depth	70 mm
Width	70 mm
Height	70 mm
Weight	0.7 kg
Type	Basic
Air consumption	0.568 l/cycle (1x up, 1x down)